

ENVIRONMENTAL PRODUCT DECLARATION

IN ACCORDANCE WITH EN
15804+A2 & ISO 14025

iCell Frónatū Insulationboard
Thermal & Acoustic Insulation
from RS EcoSaver AB (iCell)



EPD HUB, HUB-7627

Published on 24.09.2026, last updated on
24.09.2026, valid until 23.09.2031

Life Cycle Assessment study has been performed in accordance with the requirements of EN 15804, EPD Hub PCR version 1.2 (24 Mar 2025) and JRC characterization factors EF 3.1.

GENERAL INFORMATION

MANUFACTURER

Manufacturer	RS EcoSaver AB (iCell)
Address	Härkeberga Ekeby 21, 745 96 Enköping, Sweden
Contact details	info@icell.se
Website	www.icell.se

This EPD is intended for business-to-business and/or business-to-consumer communication. The manufacturer has the sole ownership, liability, and responsibility for the EPD. EPDs within the same product category but from different programs may not be comparable. EPDs of construction products may not be comparable if they do not comply with EN 15804 and if they are not compared in a building context.

EPD STANDARDS, SCOPE AND VERIFICATION

Program operator	EPD Hub, hub@epdhub.com
Reference standard	EN 15804:2012+A2:2019/AC:2021 and ISO 14025
PCR	EPD Hub Core PCR Version 1.2, 24 Mar 2025 EN 16783 Thermal insulation products
Sector	Construction product
Category of EPD	Third party verified EPD
Parent EPD number	-
Scope of the EPD	Cradle to gate with options, A5, and modules C1-C4, D
EPD author	LCA Point
EPD verification	Independent verification of this EPD and data, according to ISO 14025: ☐ Internal verification ☒ External verification
EPD verifier	Elma Avdyli as an authorized verifier for EPD Hub

PRODUCT

Product name	iCell Frónatū Insulationboard
Additional labels	-
Product reference	-
Place(s) of raw material origin	SE, GLO
Place of production	Älvdalen, Sweden
Place(s) of installation and use	Sweden
Period for data	Calendar Year 2024
Averaging in EPD	No grouping
Variation in GWP-fossil for A1-A3 (%)	-
GTIN (Global Trade Item Number)	-
NOBB (Norwegian Building Product Database)	-
A1-A3 Specific data (%)	47,2

ENVIRONMENTAL DATA SUMMARY

Declared unit	1m2 of iCell board 39 mm (Thermal resistance (R-value) is 1 m ² ·K/W.)
Declared unit mass	1,248 kg
Mass of packaging	0,15 kg
GWP-fossil, A1-A3 (kgCO₂e)	1,28
GWP-total, A1-A3 (kgCO₂e)	-0,71
Secondary material, inputs (%)	88,7
Total energy use, A1-A3 (kWh)	9,5
Net freshwater use, A1-A3 (m³)	0,01

PRODUCT AND MANUFACTURER

ABOUT THE MANUFACTURER

RS EcoSaver AB develops and manufactures cellulose-based insulation products under the iCell brand. The products are based primarily on recycled cellulose fibres and are manufactured in Sweden, with a focus on thermal performance, resource efficiency and the use of recycled and bio-based raw materials.

PRODUCT DESCRIPTION

iCell Frónatū Insulationboard is a factory-made thermal and acoustic insulation board primarily manufactured from recycled cardboard fibres.

The product combines a high proportion of secondary and bio-based raw materials with a thermal conductivity of $\lambda = 0.039 \text{ W/mK}$ and a density of approximately $32\text{-}42 \text{ kg/m}^3$.

Frónatū is suitable for thermal and acoustic insulation in new construction and renovation. The cellulose fibres are hygroscopic and can absorb and release moisture in response to changes in ambient conditions, making the product suitable for correctly designed diffusion-open building assemblies.

The product is assessed/registered in Byggvarubedomningen, BASTA and SundaHus.

Further information can be found at:
www.icell.se

PRODUCT RAW MATERIAL MAIN COMPOSITION

Raw material category	Amount, mass %	Material origin
Metals	-	-
Minerals	5	GLO
Fossil materials	7	GLO
Bio-based materials	88	SE

BIOGENIC CARBON CONTENT

Product's biogenic carbon content at the factory gate

Biogenic carbon content in product, kg C	0,45
Biogenic carbon content in packaging, kg C	0,06

FUNCTIONAL UNIT AND SERVICE LIFE

Declared unit	1m ² of iCell board 39 mm (Thermal resistance (R-value) is 1 m ² ·K/W.)
Mass per declared unit	1,248 kg/m ²
Functional unit	1m ² of iCell board 39 mm (Thermal resistance (R-value) is 1 m ² ·K/W.)
Reference service life	50 years

TECHNICAL CHARACTERISTICS

Thermal conductivity	0,039 W/mK
Density	32 kg/m ³
Reaction to Fire	E

RESULTS PER THICKNESS

Thickness (mm)	kg/m ²	R (m ² ·K/W)	GWP Fossil A1-3 (kgCO ₂ e/m ²)	GWP Total A1-3 (kgCO ₂ e/m ²)
iCell Skiva W45E	1,44	1,15	1,48	-0,82
iCell Skiva W70E	2,24	1,79	2,30	-1,27
iCell Skiva W95E	3,04	2,44	3,12	-1,73
iCell Skiva W120E	3,84	3,08	3,94	-2,18
iCell Skiva W145E	4,64	3,72	4,76	-2,64
iCell Skiva W170E	5,44	4,36	5,58	-3,09

SUBSTANCES, REACH - VERY HIGH CONCERN

Substances of very high concern	EC	CAS
Boric Acid	-	10043-35-3

PRODUCT LIFE-CYCLE

SYSTEM BOUNDARY

This EPD covers the life-cycle modules listed in the following table.

Product stage			Assembly stage		Use stage							End of life stage				Beyond the system boundaries		
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D		
x	x	x	ND	x	ND	ND	ND	ND	ND	ND	ND	x	x	x	x	x		
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstruction/ demolition	Transport	Waste processing	Disposal	Reuse	Recovery	Recycling

Not declared = ND.

MANUFACTURING AND PACKAGING (A1-A3)

The environmental impacts considered for the product stage cover the manufacturing of raw materials used in the production as well as packaging materials and other ancillary materials. Also, fuels used by machines, and handling of waste formed in the production processes at the manufacturing facilities are included in this stage. The study also considers the material losses occurring during the manufacturing processes as well as losses during electricity transmission.

A market-based approach is used in modelling the electricity mix utilized in the factory.

The use of green energy in manufacturing is demonstrated through contractual instruments (GOs, RECs, etc.), and its use is ensured throughout the validity period of this EPD.

The raw materials used in the product are transported primarily by road using heavy goods vehicles. Materials sourced from more distant locations are partly transported by sea freight. The primary raw material used in the production of the insulation is secondary material derived from recycled cardboard.

During the manufacturing process, flame retardants and a binder are added to the recycled cardboard. The binder is activated in a natural gas-fired oven. Material handling within the production facility is carried out using diesel-powered mobile equipment, while the remaining production machinery operates on electricity.

Production waste generated during the manufacturing process is collected and sent for energy recovery. The finished product is cut to the required dimensions and packaged in plastic wrapping on wooden pallets for transportation and distribution.

TRANSPORT AND INSTALLATION (A4-A5)

This EPD does not include transportation to the construction site (module A4), as project locations may vary significantly and therefore require separate assessment on a case-by-case basis.

The product is installed manually and does not require additional energy, water, or other resources during installation. Installation waste resulting from on-site cutting is estimated at 2% of the product mass. This waste is assumed to be sent for incineration at the end of the installation process.

Module A5 also includes the assessment of the treatment of packaging materials generated during installation. The environmental impacts associated with the incineration of plastic packaging and wooden pallets are included in this module.


PRODUCT END OF LIFE (C1-C4, D)

At the end of its service life, the product can be removed from the building as a separate component due to its panel-based form and dimensional stability. The energy consumption associated with the demolition and removal process (C1) has been estimated at 0.01 kWh per kilogram of product.

Following removal, the product is transported to a waste treatment facility (C2), where it is assumed to be used for energy recovery through incineration (C3). The environmental impacts associated with transportation and end-of-life treatment are included in the relevant end-of-life modules.

The benefits resulting from energy recovery, including the substitution of conventional energy production, are reported separately in Module D.

LIFE CYCLE FLOW DIAGRAM



LIFE-CYCLE ASSESSMENT

CUT-OFF CRITERIA

The study does not exclude any modules or processes which are stated mandatory in the reference standard and the applied PCR. The study does not exclude any hazardous materials or substances. The study includes all major raw material and energy consumption. All inputs and outputs of the unit processes, for which data is available for, are included in the calculation. There is no neglected unit process more than 1% of total mass or energy flows. The module specific total neglected input and output flows also do not exceed 5% of energy usage or mass.

The production of capital equipment, construction activities, and infrastructure, maintenance and operation of capital equipment, personnel-related activities, energy and water use related to company management and sales activities are excluded.

VALIDATION OF DATA

Data collection for production, transport, and packaging was conducted using time and site-specific information, as defined in the general information section on page 1 and 2. Upstream process calculations rely on generic data as defined in the Bibliography section. Manufacturer-provided specific and generic data were used for the product's manufacturing stage. The analysis was performed in One Click LCA EPD Generator, with the 'Cut-Off, EN 15804+A2' allocation method, and characterization factors according to EN 15804:2012+A2:2019/AC:2021 and JRC EF 3.1.

ALLOCATION, ESTIMATES AND ASSUMPTIONS

Allocation is required if some material, energy, and waste data cannot be measured separately for the product under investigation. All allocations are done as per the reference standards and the applied PCR. In this study, allocation has been done in the following ways:

Data type	Allocation
Raw materials	No allocation
Packaging material	Not applicable
Ancillary materials	Not applicable
Manufacturing energy and waste	No allocation

PRODUCT & MANUFACTURING SITES GROUPING

Type of grouping	No grouping
Grouping method	Not applicable
Variation in GWP-fossil for A1-A3, %	-

This EPD is product and factory specific.

LCA SOFTWARE AND BIBLIOGRAPHY

This EPD has been created using One Click LCA EPD Generator for EPD Hub V3 and EPD Process Certification v3.2.5. The LCA and EPD have been prepared according to the reference standards and ISO 14040/14044. The EPD Generator uses Ecoinvent v3.10.1/3.11/3.12 and One Click LCA databases as sources of environmental data. Allocation used in Ecoinvent 3.10.1/3.11/3.12 environmental data sources follow the methodology 'allocation, Cut-off, EN 15804+A2'.

ENVIRONMENTAL IMPACT DATA

The estimated impact results are only relative statements which do not indicate the end points of the impact categories, exceeding threshold values, safety margins or risks.

CORE ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, EF 3.1

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	C1	C2	C3	C4	D
GWP – total ¹⁾	kg CO ₂ e	-1,15E+00	8,76E-02	3,45E-01	-7,14E-01	ND	4,86E-01	4,15E-03	0,00E+00	1,69E+00	0,00E+00	-1,63E-02
GWP – fossil	kg CO ₂ e	5,00E-01	8,75E-02	6,96E-01	1,28E+00	ND	1,27E-01	4,15E-03	0,00E+00	4,16E-02	0,00E+00	-1,54E-02
GWP – biogenic	kg CO ₂ e	-1,65E+00	7,63E-06	-3,52E-01	-2,00E+00	ND	3,58E-01	0,00E+00	0,00E+00	1,65E+00	0,00E+00	-7,79E-04
GWP – LULUC	kg CO ₂ e	5,10E-04	3,36E-05	5,25E-04	1,07E-03	ND	2,33E-05	4,25E-07	0,00E+00	1,27E-05	0,00E+00	-1,38E-04
Ozone depletion pot.	kg CFC-11e	1,39E-06	1,72E-09	2,70E-08	1,42E-06	ND	2,86E-08	6,36E-11	0,00E+00	5,64E-10	0,00E+00	-2,56E-09
Acidification potential	mol H ⁺ e	2,54E-03	4,63E-04	1,57E-03	4,57E-03	ND	1,36E-04	3,75E-05	0,00E+00	3,43E-04	0,00E+00	-5,88E-04
EP-freshwater ²⁾	kg Pe	1,45E-04	5,56E-06	6,47E-05	2,16E-04	ND	5,55E-06	1,20E-07	0,00E+00	5,01E-06	0,00E+00	-4,04E-06
EP-marine	kg Ne	4,60E-04	1,15E-04	4,98E-04	1,07E-03	ND	4,30E-05	1,74E-05	0,00E+00	1,77E-04	0,00E+00	-1,72E-04
EP-terrestrial	mol Ne	4,57E-03	1,27E-03	5,03E-03	1,09E-02	ND	4,28E-04	1,90E-04	0,00E+00	1,55E-03	0,00E+00	-2,87E-03
POCP (“smog”) ³⁾	kg NMVOCe	2,59E-03	5,07E-04	2,26E-03	5,36E-03	ND	1,65E-04	5,68E-05	0,00E+00	3,93E-04	0,00E+00	-4,98E-04
ADP-minerals & metals ⁴⁾	kg Sbe	4,18E-05	2,50E-07	1,72E-06	4,38E-05	ND	8,93E-07	1,49E-09	0,00E+00	1,13E-07	0,00E+00	-4,66E-08
ADP-fossil resources	MJ	9,25E+00	1,24E+00	2,17E+01	3,22E+01	ND	7,11E-01	5,43E-02	0,00E+00	2,96E-01	0,00E+00	-1,83E-01
Water use ⁵⁾	m ³ e depr.	1,65E-01	5,94E-03	2,16E-01	3,87E-01	ND	1,61E-02	1,36E-04	0,00E+00	9,12E-02	0,00E+00	-1,48E-02

1) GWP = Global Warming Potential; 2) EP = Eutrophication potential. Required characterisation method and data are in kg P-eq. Multiply by 3,07 to get PO₄e; 3) POCP = Photochemical ozone formation; 4) ADP = Abiotic depletion potential; 5) EN 15804+A2 disclaimer for Abiotic depletion and Water use and optional indicators except Particulate matter and Ionizing radiation, human health. The results of these environmental impact indicators shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.

ADDITIONAL (OPTIONAL) ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, EF 3.1

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	C1	C2	C3	C4	D
Particulate matter	Incidence	2,85E-08	6,47E-09	2,60E-08	6,10E-08	ND	1,74E-09	1,07E-09	0,00E+00	2,89E-09	0,00E+00	-8,22E-09
Ionizing radiation ⁶⁾	kBq U235e	3,20E-02	1,56E-03	5,62E-01	5,96E-01	ND	1,20E-02	2,41E-05	0,00E+00	5,65E-04	0,00E+00	-1,22E-03
Ecotoxicity (freshwater)	CTUe	2,27E+00	1,55E-01	5,60E+00	8,03E+00	ND	2,40E-01	2,99E-03	0,00E+00	2,16E+00	0,00E+00	-1,43E-01
Human toxicity, cancer	CTUh	1,27E-10	1,47E-11	5,87E-10	7,29E-10	ND	2,35E-11	4,27E-13	0,00E+00	1,02E-10	0,00E+00	-4,73E-11
Human tox. non-cancer	CTUh	6,01E-09	7,24E-10	2,75E-09	9,49E-09	ND	6,76E-10	6,76E-12	0,00E+00	4,08E-09	0,00E+00	-1,65E-09
SQP ⁷⁾	-	1,51E+00	8,58E-01	4,72E+01	4,95E+01	ND	1,02E+00	3,81E-03	0,00E+00	8,95E-02	0,00E+00	-1,05E+01

6) EN 15804+A2 disclaimer for Ionizing radiation, human health. This impact category deals mainly with the eventual impact of low-dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator; 7) SQP = Land use related impacts/soil quality.

USE OF NATURAL RESOURCES

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	C1	C2	C3	C4	D
Renew. PER as energy ⁸⁾	MJ	4,81E-01	2,08E-02	4,70E+00	5,20E+00	ND	-2,48E+00	3,44E-04	0,00E+00	-2,22E+01	0,00E+00	-2,52E+00
Renew. PER as material	MJ	0,00E+00	0,00E+00	3,14E+00	3,14E+00	ND	-3,14E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Total use of renew. PER	MJ	4,81E-01	2,08E-02	7,84E+00	8,34E+00	ND	-5,62E+00	3,44E-04	0,00E+00	-2,22E+01	0,00E+00	-2,52E+00
Non-re. PER as energy	MJ	7,53E+00	1,24E+00	2,01E+01	2,89E+01	ND	-5,72E-01	5,43E-02	0,00E+00	2,96E-01	0,00E+00	-1,83E-01
Non-re. PER as material	MJ	1,72E+00	0,00E+00	1,49E+00	3,21E+00	ND	-1,50E+00	0,00E+00	0,00E+00	-1,71E+00	0,00E+00	0,00E+00
Total use of non-re. PER	MJ	9,25E+00	1,24E+00	2,16E+01	3,21E+01	ND	-2,07E+00	5,43E-02	0,00E+00	-1,41E+00	0,00E+00	-1,83E-01
Secondary materials	kg	1,11E+00	5,51E-04	1,17E-02	1,12E+00	ND	2,25E-02	2,26E-05	0,00E+00	4,34E-04	0,00E+00	-2,20E-04
Renew. secondary fuels	MJ	2,12E-05	5,86E-06	8,38E-02	8,38E-02	ND	1,68E-03	5,90E-08	0,00E+00	7,13E-06	0,00E+00	-1,31E-06
Non-ren. secondary fuels	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Use of net fresh water	m ³	3,85E-03	1,67E-04	5,04E-03	9,06E-03	ND	2,58E-04	3,59E-06	0,00E+00	1,45E-03	0,00E+00	-6,72E-05

8) PER = Primary energy resources.

END OF LIFE – WASTE

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	C1	C2	C3	C4	D
Hazardous waste	kg	2,94E-02	1,72E-03	2,07E-02	5,18E-02	ND	3,17E-03	6,05E-05	0,00E+00	2,19E-02	0,00E+00	-2,77E-03
Non-hazardous waste	kg	2,18E+00	3,56E-02	1,40E+00	3,62E+00	ND	2,63E-01	8,24E-04	0,00E+00	1,22E+00	0,00E+00	-3,14E-02
Radioactive waste	kg	7,94E-06	3,88E-07	1,33E-04	1,41E-04	ND	2,84E-06	5,90E-09	0,00E+00	1,33E-07	0,00E+00	-3,00E-07

END OF LIFE – OUTPUT FLOWS

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	C1	C2	C3	C4	D
Components for re-use	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Materials for recycling	kg	0,00E+00	0,00E+00	2,26E-02	2,26E-02	ND	4,52E-04	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Materials for energy rec	kg	0,00E+00	0,00E+00	8,24E-03	8,24E-03	ND	1,83E-01	0,00E+00	0,00E+00	1,25E+00	0,00E+00	0,00E+00
Exported energy	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	0,00E+00	0,00E+00	0,00E+00	4,46E+00	0,00E+00	0,00E+00
Exported energy – Electricity	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	0,00E+00	0,00E+00	0,00E+00	3,60E-01	0,00E+00	0,00E+00
Exported energy – Heat	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	0,00E+00	0,00E+00	0,00E+00	4,10E+00	0,00E+00	0,00E+00

ADDITIONAL INDICATOR – GWP-GHG

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	C1	C2	C3	C4	D
GWP-GHG ⁹⁾	kg CO ₂ e	5,00E-01	8,76E-02	6,97E-01	1,28E+00	ND	1,27E-01	4,15E-03	0,00E+00	4,16E-02	0,00E+00	-1,55E-02

9) This indicator includes all greenhouse gases excluding biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product. In addition, the characterisation factors for the flows – CH₄ fossil, CH₄ biogenic and Dinitrogen monoxide – were updated. This indicator is identical to the GWP-total of EN 15804:2012+A2:2019 except that the characterisation factor for biogenic CO₂ is set to zero

SCENARIO DOCUMENTATION

DATA SOURCES

Manufacturing energy scenario documentation

1. Electricity production, wind, >3MW turbine, onshore, Sweden, Ecoinvent, 0.0277 kgCO₂e/kWh
2. Electricity production, nuclear, pressure water reactor, Sweden, Ecoinvent, 0.0070 kgCO₂e/kWh
3. Electricity, medium voltage, residual mix, Sweden, Ecoinvent, 0.0836 kgCO₂e/kWh
4. Electricity production, hydro, run-of-river, Sweden, Ecoinvent, 0.0044 kgCO₂e/kWh
5. Diesel, burned in building machine, World, Ecoinvent, 0.10 kgCO₂e/MJ
6. Heat production, natural gas, at industrial furnace >100kW, Sweden, Ecoinvent, 0.0754 kgCO₂e/MJ
7. Electricity production, photovoltaic, 570kWp open ground installation, multi-Si, Sweden, Ecoinvent, 0.0806 kgCO₂e/kWh

Installation at the building site (A5) - Scenario documentation

Scenario parameter	Value
Energy: type and consumption (MJ or kWh)	-
Water use (m ³)	-
Ancillary materials: type and mass (kg)	-
Waste materials: type and mass (kg)	0,13 kg wood from pallet 0,024 kg insulation (cellulose) from installation loss 0,031 kg of PE from package
Waste materials: output routes	Wood 100 % incineration PE 100 % incineration Insulation (cellulose) 100 % incineration
Direct emissions (kg)	-

End of life (C1-C4) - Scenario documentation

Scenario information	Value
Collection process: collected separately (kg)	1,248 kg
Collection process: Mixed waste (kg)	-
Recovery: re-use (kg)	0
Recovery: recycling (kg)	0
Recovery: energy recovery (kg)	1,248 kg
Disposal (kg)	0
Scenario assumptions e.g. transportation (mode, km) & other	50-150 km truck

THIRD-PARTY VERIFICATION STATEMENT

EPD Hub declares that this EPD is verified in accordance with ISO 14025 by an independent, third-party verifier. The project report on the Life Cycle Assessment and the report(s) on features of environmental relevance are filed at EPD Hub. EPD Hub PCR and ECO Platform verification checklist are used.

EPD Hub is not able to identify any unjustified deviations from the PCR and EN 15804+A2 in the Environmental Product Declaration and its project report.

EPD Hub maintains its independence as a third-party body; it was not involved in the execution of the LCA or in the development of the declaration and has no conflicts of interest regarding this verification.

The company-specific data and upstream and downstream data have been examined as regards plausibility and consistency. The publisher is responsible for ensuring the factual integrity and legal compliance of this declaration.

The software used in creation of this LCA and EPD is verified by EPD Hub to conform to the procedural and methodological requirements outlined in ISO 14025:2010, ISO 14040/14044, EN 15804+A2, and EPD Hub Core Product Category Rules and General Program Instructions.

Verified tools

Tool verifier: Magaly Gonzalez Vazquez

Tool verification validity: 27 March 2025 - 26 March 2028

Elma Avdyli as an authorized verifier for EPD Hub Limited 24.09.2026

